

Soar® Series High Mast LED Floodlight



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations

CE

IP66

ROHS

960W, 130,000 lumens

120-277V or 277-480V

4000K, 5000K, 5700K

Field rotatable optics (0 - 350° rotation)

+/- 5° tilt, fits mast arm 1.65 - 2.375 inch (42 - 60 mm OD)

EPA (wind load) 1.69 sq. ft (.15 m2)

Type 4 & Type 5 Optics

Highland® Series High Mast & Large Area LED



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 8750 for LED Equipment
- CSA C22.2 No. 250.0

DLC

International Dark Sky Association approved (WW options)

IP66 (without twist-lock receptacle)

HL-250 - 265W, 40,000 lumens

HL-500 - 530W, 80,000 lumens

90 - 305 VAC, 50/60Hz (120-277V)

249 - 528 VAC, 50/60Hz (277-480V)

3000K, 4000K, 5000K

EPA 250 model - 0.96 sq. ft. (0.09 m2)

EPA 500 model - 1.21 sq. ft. (0.11 m2)

Type 2, Type 4, Type 5 optics

Narrow Spot, Medium Spot & Wide Spot

Guard Pro™ Series

Hazardous Rated LED Floodlight



ETL/cEL Certified to:

- UL1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Location
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 1 Groups E, F, G
- Class II, Division 2 Groups F & G
- Class III

IP66, ABS (pending)

Up to 2,600 lumens - 20W (LO)

Up to 5,200 lumens - 40W (LO)

Up to 7,800 lumens - 60W (LO)

Up to 13,000 lumens - 100W (HI)

Up to 19,500 lumens - 150W (HI)

Up to 26,000 lumens - 200W (HI)

ModCom® 3 Series Hazardous Rated LED Floodlight



Robust construction ideal for up 6G
high vibration, high temperature and
hazardous applications

ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Location
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 2 Groups F & G

CE, ABS, IP67, IPD

Up to 15,000 lumens - 121W (LO)

Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



EcoMod® 3 Series Heavy Duty LED Floodlight



Expertly engineered with durable, marine
grade components and various optic options

ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)

CE, IP66, ABS

Up to 15,000 lumens - 121W (LO)


Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



Defend™ Flood 2

Aimable in 15° increments
Mounting ceiling, wall or pendant



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
- UL 844 Hazardous Locations
- Class I, Division 1 Groups C & D
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 1 Groups E, F, G
- Class II, Division 2 Groups F, G
- Class III

IP66, IK10, ABS (pending)

5,600 lumens - 40W

8,400 lumens - 60W

14,000 lumens - 100W

28,000 lumens - 200W

120-277V, 277-480V, 1-10V dimming

6kV surge protection

Command Flood® Series Industrial LED Floodlight

Adjustable 316 stainless steel mounting harp (SSHHP)
Adj. waterline security bracket (NPL) (CF-150 only)



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
- CSA C22.2 No. 250.0

CE, IP66, ABS

CF-150, 145W, 18,500 lumens

CF-250, 240W, 32,000 lumens

CF-375, 360W, 48,000 lumens

Very Narrow Spot, Spot, Medium Flood and Wide Flood Optics



Wayfinder™ 2 LED Accessway Light

Integrated EMB option (pending)
Pathway/walkway/overdoor light



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 924 EMB option (pending)

ABS (pending)

IP66

DLC

3.2W - 11W (field adjustable output), up to 1300 lumens

SubM compliant 2-HR EMB and 6-HR EMB options

Colored (red, green, blue) and diffused lens options

Metallic LED VP Series Vaporproof Fixture

Wall (bulkhead) mount
Ceiling mount



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Saltwater
- UL 844 Hazardous Location

Class I, Division 2 Groups A, B, C, D

Class I, Zone 2 T3A, 180°C max surf temp

Class II, Division 2 Groups F, G

T4A, 120°C max surf temp

IP66, ABS

17W, 1300 lumens

5600K and 3000K options

Sealed in optically clear silicone

100-277V, 0-10V dimming



Midline™ Flood 2

Made to withstand moisture, shock and vibration of marine environments



Available in medium flood or wide flood optic options

Available with a 360° adjustable, stainless steel bracket and hardware

UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
- CSA C22.2 No. 250.0

CE, IP66, IK08, ABS (pending)

FCC Part 15, Subpart B, Class A standards for conduct and radiated emissions.

RoHS compliant

Up to 90W - 7000, 9000, 12000 lumens

5000K

120-347V

Cube-Light Compact LED Area Light

Wall (bulkhead) mount
Ceiling mount



ETL/cETL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)

CE, ABS, IP66 rated

Impact-resistant, polycarbonate


Red, green, blue and amber

13W, 1000 lumens

Conformal coated

CVO 2 LED Area & Conveyor Light

Wall or pole mount capable



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
Class I, Division 2 Groups A, B, C, D
Class II, Division 2 Groups F & G
Class III, Division 2

T5, 100°C maximum surface temperature

• CSA C22.2 No. 250.0

• CSA C22.2 No. 137

CE

UKCA

IP66

NEMA 4X

DLC

International Dark Sky Association approved (2200K and Amber models only)

FCC Part 15, Subpart B, Class A standards for conducted and radiated emissions

RoHS compliant

In accordance with Chilean regulations of Supreme Decree No. 1 of 2022 (2200K contains less than 7% blue light and Amber contains less than 1% blue light)

Type II (T2), Type III (T3), Type V (T5) optic, Full cutoff, zero uplight

Up to 75W, field adjustable output

Up to 11000 (50K), 8000 (22K) or 6500 (Amber) lumens

Apex™ Series

High Mast LED Floodlight



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations

IP66, IK08, FCC Part 15 Class A, CE

APEX-600 - 600W, 85,000 lumens

APEX-1000 - 1000W, 138,000 lumens

120-277V, 277-480V, 50/60Hz

3000K, 4000K, 5000K, 5700K

10° NEMA 2x2, 30° NEMA 4x4, 60° NEMA 6x6 Optics