

# PHOENIX PRODUCTS LLC

## TEST REPORT

### SCOPE OF WORK

LED Performance Testing

### MODEL NUMBER

CF-250-WF-120-277-NW

### PROJECT NUMBER

G104357589

### REPORT NUMBER

104357589CHI-033

### ISSUE DATE

2/19/2021

### REVISED DATE

None

### TEST DATES

02/10/2021.

### DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



**REPORT NUMBER**

104357589CHI-033

**MODEL NUMBER(s)**

CF-250-WF-120-277-NW

**REPORT RENDERED TO:**

PHOENIX PRODUCTS LLC  
8711 W PORT AVE.  
MILWAUKEE, WI, 53224  
USA

**STATEMENT OF LIMITATION**

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

**AUTHORIZATION**

The testing performed was authorized by signed quote number Qu-01080058-1.

**TEST STANDARDS**

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

In Charge of Testing:



Ian Smith  
Engineer  
Lighting Division

Reviewer:



Jeff Davis  
NA Technical Lead  
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## SAMPLE INFORMATION

REPORT NO. 104357589CHI-033



## ITEMS RECEIVED

| Item No. | Control No.      | Model No.            | Description       | Type       | Received  |
|----------|------------------|----------------------|-------------------|------------|-----------|
| 1        | AH01272021125026 | CF-250-WF-120-277-NW | Command Flood 250 | Production | 1/27/2021 |

## TESTED SAMPLE CONFIGURATIONS

| Config No. | Tested Model No.     | Item Nos. Utilized |
|------------|----------------------|--------------------|
| 1          | CF-250-WF-120-277-NW | 1                  |

## SAMPLE PHOTOS - TESTED CONFIGURATIONS



## SUMMARY

REPORT NO. 104357589CHI-033

### PRODUCT INFORMATION AND SUMMARY OF DATA

|                      |                              |
|----------------------|------------------------------|
| Product Model No.:   | CF-250-WF-120-277-NW         |
| Product Description: | Command Flood 250            |
| LED Model No.:       | Lumileds 5050                |
| Driver Model No.:    | Inventronics / EUM-240S350DT |
| Light Source:        | LED                          |

| Criteria                           | Results |
|------------------------------------|---------|
| Light Output (lumens)              | 31149.0 |
| Input Power (W) @ 120 (Vac)        | 239.64  |
| Lumen Efficacy (lm/W)              | 130.0   |
| Input Power Factor ( ) @ 120 (Vac) | 0.998   |

## TEST METHODS

### SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

### TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

**TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING**

**REPORT NO. 104357589CHI-033**

| Test Configuration | Tested Model No.     | Pass/Fail/NA |
|--------------------|----------------------|--------------|
| 1                  | CF-250-WF-120-277-NW | NA           |

**PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)**


| Base Orientation | Input Voltage (Vac) | Input Current (mA) | Input Power (W) | Input Power Factor (I) |
|------------------|---------------------|--------------------|-----------------|------------------------|
| Up               | 120.1               | 1999.4             | 239.64          | 0.998                  |

| Light Output (lm) | Lumen Efficacy (lm/W) |
|-------------------|-----------------------|
| 31149.0           | 130.0                 |

**INTENSITY SUMMARY - CANDELA**


| Angle | 0     | 22.5  | 45    | 67.5  | 90    |
|-------|-------|-------|-------|-------|-------|
| 0     | 15692 | 15692 | 15692 | 15692 | 15692 |
| 5     | 16392 | 16443 | 16267 | 16076 | 15922 |
| 10    | 17338 | 16928 | 16651 | 16218 | 15712 |
| 15    | 17286 | 16496 | 16054 | 15505 | 14641 |
| 20    | 16399 | 15773 | 15332 | 14846 | 14152 |
| 25    | 14607 | 14367 | 14099 | 13872 | 13302 |
| 30    | 13004 | 13112 | 12872 | 12739 | 12452 |
| 35    | 11424 | 11489 | 11351 | 11316 | 11136 |
| 40    | 9700  | 9622  | 9453  | 9384  | 9361  |
| 45    | 7770  | 7384  | 7308  | 7219  | 7231  |
| 50    | 5731  | 5286  | 5255  | 5174  | 5098  |
| 55    | 3888  | 3727  | 3709  | 3625  | 3672  |
| 60    | 2714  | 2596  | 2663  | 2524  | 2557  |
| 65    | 1819  | 1783  | 1777  | 1677  | 1685  |
| 70    | 1077  | 1072  | 1069  | 1014  | 970   |
| 75    | 638   | 621   | 619   | 599   | 546   |
| 80    | 310   | 292   | 299   | 290   | 257   |
| 85    | 78    | 68    | 79    | 89    | 75    |
| 90    | 0     | 0     | 0     | 0     | 0     |
| 95    | 0     | 0     | 0     | 0     | 0     |
| 100   | 0     | 0     | 0     | 0     | 0     |
| 105   | 0     | 0     | 0     | 0     | 0     |
| 110   | 0     | 0     | 0     | 0     | 0     |
| 115   | 0     | 0     | 0     | 0     | 0     |
| 120   | 0     | 0     | 0     | 0     | 0     |
| 125   | 0     | 0     | 0     | 0     | 0     |
| 130   | 0     | 0     | 0     | 0     | 0     |
| 135   | 0     | 0     | 0     | 0     | 0     |
| 140   | 0     | 0     | 0     | 0     | 0     |
| 145   | 0     | 0     | 0     | 0     | 0     |
| 150   | 0     | 0     | 0     | 0     | 0     |
| 155   | 0     | 0     | 0     | 0     | 0     |
| 160   | 0     | 0     | 0     | 0     | 0     |
| 165   | 0     | 0     | 0     | 0     | 0     |
| 170   | 0     | 0     | 0     | 0     | 0     |
| 175   | 0     | 0     | 0     | 0     | 0     |
| 180   | 0     | 0     | 0     | 0     | 0     |

Entire luminous intensity matrix found in .IES file



REPORT NO. 104357589CHI-033

ILLUMINANCE SUMMARY



ZONAL LUMENS

| Zonal Lumen Summary |          |           |         |        |       |
|---------------------|----------|-----------|---------|--------|-------|
| Zone                | Lumens   | Luminaire | Zone    | Lumens | Total |
| 0-30                | 12,442.4 | 39.9%     | 0-10    | 1544.9 | 5.0%  |
| 0-40                | 19,488.6 | 62.6%     | 10-20   | 4457.8 | 14.3% |
| 0-60                | 28,556.2 | 91.7%     | 20-30   | 6439.6 | 20.7% |
| 60-90               | 2,592.8  | 8.3%      | 30-40   | 7046.2 | 22.6% |
| 70-100              | 818.1    | 2.6%      | 40-50   | 5670.9 | 18.2% |
| 90-120              | 0.0      | 0.0%      | 50-60   | 3396.7 | 10.9% |
| 0-90                | 31,149.0 | 100.0%    | 60-70   | 1774.6 | 5.7%  |
| 90-180              | 0.0      | 0.0%      | 70-80   | 690.4  | 2.2%  |
| 0-180               | 31,149.0 | 100.0%    | 80-90   | 127.8  | 0.4%  |
|                     |          |           | 90-100  | 0.0    | 0.0%  |
|                     |          |           | 100-110 | 0.0    | 0.0%  |
|                     |          |           | 110-120 | 0.0    | 0.0%  |
|                     |          |           | 120-130 | 0.0    | 0.0%  |
|                     |          |           | 130-140 | 0.0    | 0.0%  |
|                     |          |           | 140-150 | 0.0    | 0.0%  |
|                     |          |           | 150-160 | 0.0    | 0.0%  |
|                     |          |           | 160-170 | 0.0    | 0.0%  |
|                     |          |           | 170-180 | 0.0    | 0.0%  |

## EQUIPMENT LIST

**REPORT NO. 104357589CHI-033**

| # | Equipment                        | Model No | Control No. | Last Cal  | Cal Due   |
|---|----------------------------------|----------|-------------|-----------|-----------|
| 1 | Yokogawa Power Meter             | WT210    | 146919      | 7/1/2020  | 7/1/2021  |
| 2 | Omega Thermometer                | DPI8-C24 | 146920      | 10/1/2020 | 10/1/2021 |
| 3 | LSI High Speed Mirror Goniometer | 6440T    | 146928      | VBU       | VBU       |
| 4 | Newport Thermohygrometer         | iServer  | 146958      | 9/30/2020 | 9/30/2021 |
| 5 | Pacific AC Power Supply          | 118-ACX  | CHI0153     | VBU       | VBU       |

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

## REVISION HISTORY

| #   | Revision Date | Updated By | Reviewed By | Description of Change |
|-----|---------------|------------|-------------|-----------------------|
| --- | None          | ---        | ---         | ---                   |
| --- | ---           | ---        | ---         | ---                   |
| --- | ---           | ---        | ---         | ---                   |