

## Portable Explosion-proof LED Floodlight



Explosion-proof portable LED floodlight rated for hazardous and wet locations

For use in chemical plants, drilling rigs, refineries and other hazardous locations

LED technology increases efficiency, eliminates maintenance and supports green initiatives

### Key Applications

Chemical plants  
Drilling rigs  
Refineries  
Grain processing and storage facilities  
Wastewater treatment plants  
Power plants  
Fuel depots  
Food and beverage processing facilities

### Compliances

ETL/cETL Certified to:

- UL 844 Suitable for Hazardous Locations
  - Class I, Division 1 Groups C & D
  - Class I, Division 2 Groups A, B, C & D
  - Class II, Divisions 1 & 2 Groups F & G
  - Class III, Divisions 1 & 2
  - T4A (120°C) Temperature Rating
- CSA C22.2 No. 250.0, 94.0, 213.0, 137.0, 30.0

NEMA 4X

Buy American Act (BAA)

Build America Buy America Act (BABA)

### Specifications

<b>Construction</b>	Marine grade cast aluminum shell, cover and sealed fittings Marine grade wrought aluminum handle bracket Threaded joints are lubricated with non-drying petrolatum
<b>Finish</b>	Yellow thermoset powder coat
<b>Hardware</b>	Stainless steel
<b>Lens</b>	¾ inch thick tempered glass
<b>Light source</b>	Up to 4600 lumens, 44W Various optics available CCT 5000K 50,000 hour rated life
<b>Power source</b>	120-277V, 50-60Hz Fully potted, replaceable driver Over-voltage, over-current and short-circuit protection
<b>Power factor</b>	> 0.9
<b>Wiring</b>	Supplied with 50 feet of 16/3 type SOW cord Wire entrance is factory sealed
<b>Mounting</b>	Portable base has three holes Marine grade wrought aluminum base and harp
<b>Ambient operating temperature</b>	-20°C to +40°C
<b>Weight</b>	Fixture: 21.5 lb (9.8 kg) Packaged: 24.2 lb (11.0 kg)
<b>Warranty</b>	5 years

For IES files, see website or contact factory



This product complies with domestic preference requirements such as BABA. For additional information, visit [phoenixlighting.com](http://phoenixlighting.com) or consult your representative.





This product complies with domestic preference requirements such as BAA or TAA. For additional information, visit [phoenixlighting.com](http://phoenixlighting.com) or consult your representative.

# SLXP LED

## Portable Explosion-proof LED Floodlight

### Dimensions

---



## Ordering Information

Example: SLXPLED-FL-V3

Fixture	Optics	Generation
SLXPLED	FL	V3
	SP	
	WS	
	VS	
	OV	

### Optics

- FL 55° flood optic
- SP 25° spot optic
- WS 35° wide spot optic
- VS 15° very narrow optic
- OV 45° x 15° oval optic


### Generation

- V3 Version 3

**Special Projects:** We may be able to accommodate your special projects, so please don't hesitate to ask about additional options. Minimum order quantities and/or extended lead times will apply. Contact your Phoenix representative with specific inquiries.

## Isolux Charts

SLXP LED - Flood



SLXP LED - Spot

