

STS, RTG and Mobile Crane Lighting

EcoMod[®] 3 Series Heavy Duty LED Floodlight

Expertly engineered with durable, marine grade components and various optic options



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations

CE, IP66, ABS

EM3-LO 121W - 15,000 lumens

EM3-HI 231W - 30,000 lumens

EM3-MAX 438W - 52,500 lumens

Command Flood[®] Series LED Floodlight

Rugged design to withstand moisture and corrosion in marine and industrial installations



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
 - UL 1598A Marine (Saltwater)
- CE, IP66, ABS

CF-125 120W - 15,300 lumens

CF-250 240W - 32,000 lumens

CF-375 360W - 48,000 lumens

High Mast & Yard Lighting

Soar[™] Series High Mast & Large Area LED

EPA 1.69sq.ft
120-277V and 277-480V 0-10V



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- CE, IP66, ROHS

960W - 130,000 lumens

5700K, 5000K, 4000K

Type 4 & Type 5 Field Rotatable Optics

+/-5 ° tilt

CLIR[™] Series High Performance LED Floodlight

Visor and extended visor options



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- DLC IP66

630W - 85,000 lumens

4000K

200-480V 0-1 OV

Medium Flood and Narrow Optics

Highland Series High Mast & Area LED Floodlight

Narrow spot, medium spot, wide spot,
Type II, Type IV Type V optics Trunnion or
2.0" slipfitter mount



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
 - UL 8750 for LED Equipment
- International Dark Sky Association approved (WW options)
IP66 (without twist-lock receptacle)

250 model - 265W - 40,000 lumens

500 model - 530W - 80,000 lumens

3000K, 4000K, 5000K

120-277V, 277-480V 0-1 OV

General Lighting

Wayfinder™ 2 LED Accessway Light

Integrated EMB option (pending)
Pathway/walkway/overdoor light



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 924 EMB option (pending)

ABS (pending)

IP66

DLC

3.2W - 11W (field adjustable output), up to 1300 lumens

SubM compliant 2-HR EMB and 6-HR EMB options

Colored (red, green, blue) and diffused lens options

HDL-LED Series

90-minute run time EMB



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations

Class I, Division 2 Groups A, B, C, D

Class I, Zone 2 Group IIC

T3C - 160°C maximum surface temperature

CE, ABS, IP67 rated

HDL1 - 28W, 2850 lumens

HDL2 - 55W, 5700 lumens

HDL3 - 83W, 8550 lumens

120-277V, 277-480V

Cube-Light Compact LED Area Light

Wall (bulkhead) mount
Ceiling mount



ETL/cETL Listed to:

- UL 1598 Wet Locations
- UL 1598A Marine (Saltwater)

CE, ABS, IP66 rated

Impact-resistant, polycarbonate

Red, green, blue and amber

13W, 1000 lumens

Conformal coated

Midline™ Flood

Made to withstand moisture, shock and vibration
of marine environments



Available in medium flood or wide flood optic options

Available with a 360° adjustable, stainless steel
bracket and hardware

78W - 9200 lumens

3000K, 5000K

120-277V

Sturdilite® Master Series

Amber and RED LEDs available
No-Glare optic option



CE

IP68

IP69K

IK06 (glass)

IK10 (polycarbonate)

HI - 64W, 7600 lumens

MED - 48W, 5000 lumens

LO - 24W, 2500 lumens

12-48V DC; 24-48V DC

Spot (SP), Flood (FL), Elliptical (EP), and No-Glare (NG) optical patterns

ReadiLED™ Series

90-minute run time EMB available
on 4-foot model



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598C LED Retrofit Conversion (retrofit kits only)
- UL 1598A Marine (Saltwater)
- UL 924 Emergency Lighting Equipment

ABS, IP65, CE


2 foot - 40W, up to 4200 lumens

4 foot - 80W, up to 8400 lumens

120-277V, 50/60HZ

Danger Light™ Heavy Duty LED

RED and Green LED options



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
 - UL 1598A Marine Saltwater
 - CSA C22.2 No. 250.0
- CE, IP66

DNG1 - RED 1900 lumens, Green 2050 lumens

DNG2 - RED 3800 lumens, Green 4100 lumens

Highmast poles, lowering rings, motors and accessories available. Please ask us!