

## ModCom® 3 Series Hazardous Area Flood Light

Robust construction ideal for up to 6G high vibration, high temperature and hazardous applications



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 2 Groups F & G
- Class III

CE, ABS, IP67, IP69K

Up to 15,000 lumens - 121W (LO)

Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



## Defend™ Flood

Aimable in 15° increments  
Mounting ceiling, wall or pendant



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 844 Hazardous Locations
- Class I, Division I Groups C & D
- T5, 100°C maximum surface temperature
- IP66, TAA

Up to 14,000 lumens - 100W

Up to 23,500 lumens - 165W

120-277V, 347-480V, 1-10V

6kV surge protection

## HDL-LED Linear

90-minute run time EMB  
1100 lumens



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations

Class I, Division 2 Groups A, B, C, D

Class I, Zone 2 Group IIC

T3C - 160°C maximum surface temperature

CE, ABS, IP67 rated

HDL1 - 28W, 2850 lumens

HDL2 - 55W, 5700 lumens

HDL3 - 83W, 8550 lumens

120-277V, 277-480V



## EcoMod® 3 Series Heavy Duty Flood Light

Expertly engineered with durable, marine grade components and various optic options



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)

CE, IP66, ABS

Up to 15,000 lumens - 121W (LO)

Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



## LFXB Linear

90-minute run time EMB available  
on 4-foot model



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations

Class I, Division 1 Groups C & D

T6, 85°C maximum surface temperature

Class II, Division 1 Groups E, F & G

T3B, 165°C maximum surface temperature

Class III

- UL 924 Emergency Lighting Equip

2 foot - 40W, up to 4200 lumens


4 foot - 80W, up to 8400 lumens

120-277V, 50/60Hz



## Metallic LED VP

Wall (bulkhead) mount  
Ceiling mount



UL/cUL Certified to:

- UL1598 Suitable for Wet Locations
- UL 1598A Marine Saltwater
- UL 844 Hazardous Locations

Class I, Division 2 Groups A, B, C, D

Class I, Zone 2 T3A, 180°C maximum surface temperature

Class II, Division 2 Groups F, G

T4A, 120°C maximum surface temperature

IP66, ABS

17W, 1300 lumens

5600K and 3000K options

Sealed in optically clear silicone.

100-277V 0-10V dimming



## CVO 2 LED Area & Conveyor Light

Wall or pole mount capable



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)

CSA C22.2 No. 250.0

CE

UKCA

IP66

NEMA 4X

International Dark Sky Association approved (2200K and Amber models only)

FCC Part 15, Subpart B, Class A standards for conducted and radiated emissions

RoHS compliant

Type II (T2), Type III (T3), Type V (T5) optic, Full cutoff, zero uplight

Up to 75W, field adjustable output

Up to 11000 (50K), 8000 (22K) or 6500 (Amber) lumens

## Conquer™ Series Flood

Driverless technology 120 or 277v.

High Temperature up to 85°C



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 844 Hazardous Locations (-40°C to +40°C)

Class I, Division 2 Groups A, B, C, D

T4, 135°C (275°F) maximum surface temperature

Class II, Division 2 Groups F, G

IP67, NEMA 6

10 mm tempered glass - standard

Domed clear or diffuse polycarb lens

60W, 6000 lumens 5000K

COB technology

## Wayfinder™ 2 LED Accessway Light

Integrated EMB option (pending)

Pathway/walkway/overdoor light



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 924 EMB option (pending)

ABS (pending)

IP66

DLC

3.2W - 11W (field adjustable output), up to 1300 lumens

SubM compliant 2-HR EMB and 6-HR EMB options

Colored (red, green, blue) and diffused lens options

## Cube-Light

Wall (bulkhead) mount

Ceiling mount



ETL/cETL Listed to:

- UL 1598 Wet Locations
- UL 1598A Marine (Saltwater)

CE, ABS, IP66 rated

Impact-resistant, polycarbonate

Red, green, blue and amber

13W, 1000 lumens

Conformal coated

## Conquer™ Series Linear

Driverless technology 120 or 277v.

High Temperature up to 85°C



UL/cUL Listed to:

- UL 1598 Wet Locations
- UL 844 Hazardous Locations (-40°C to +55°C)

Class I, Division 2 Groups A, B, C, D

T4, 135°C (275°F) maximum surface temperature

Class II, Division 2 Groups F, G

T4A, 120°C (248°F) maximum surface temperature

Class III

IP67, NEMA

2ft - 60W 6600 lumens

4ft - 80W 4ft 9400 lumens

5000K 120V or 277V

-40°C to +85°C

## ReadiLED™ Series

90-minute run time EMB available

on 4-foot model



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598C LED Retrofit Conversion (retrofit kits only)
- UL 1598A Marine (Saltwater)
- UL 924 Emergency Lighting Equipment

ABS, IP65, CE

2 foot - 40W, up to 4200 lumens

4 foot - 80W, up to 8400 lumens

120-277V, 50/60HZ

## SLX/SLXP/DLX

Available as Dock Light, Floodlight,

Portable Task Light



ETL/cETL Certified to:

- UL 1598 Ordinary Locations
- UL 1598A (Saltwater)
- UL 844 Suitable for Hazardous Locations

Class I, Division 1 Groups C & D

Class I, Division 2 Groups A, B, C & D

Class II, Divisions 1 & 2 Groups F & G

Class III, Divisions 1 & 2

- NEMA 4X

44W, 3800 lumens 5000K

Conformal coated modules

Flood (45°) and spot (28°)

