

ModCom® 3 Series Hazardous Area Flood Light

Robust construction ideal for up to 6G high vibration, high temperature and hazardous applications



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 2 Groups F & G
- Class III



CE, ABS, IP67, IP69K

Up to 15,000 lumens - 121W (LO)

Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)

Defend™ Flood

Aimable in 15° increments
Mounting ceiling, wall or pendant



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
 - UL 844 Hazardous Locations
- Class I, Division I Groups C & D
T5, 100°C maximum surface temperature
IP66, TAA

Up to 14,000 lumens - 100W

Up to 23,500 lumens - 165W

120-277V, 347-480V, 1-10V

6kV surge protection

HDL-LED Linear

90-minute run time EMB
1100 lumens



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations



Class I, Division 2 Groups A, B, C, D

Class I, Zone 2 Group IIC

T3C - 160°C maximum surface temperature

CE, ABS, IP67 rated

HDL1 - 28W, 2850 lumens

HDL2 - 55W, 5700 lumens

HDL3 - 83W, 8550 lumens

120-277V, 277-480V

EcoMod® 3 Series Heavy Duty Flood Light

Expertly engineered with durable, marine grade components and various optic options



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)

CE, IP66, ABS

Up to 15,000 lumens - 121W (LO)

Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



LFXB Linear

90-minute run time EMB available
on 4-foot model



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
 - UL 1598A Marine (Saltwater)
 - UL 844 Hazardous Locations
- Class 1, Division 1 Groups C & D
T6, 85°C maximum surface temperature
Class II, Division 1 Groups E, F & G
T3B, 165°C maximum surface temperature
Class III

- UL 924 Emergency Lighting Equip

2 foot - 40W, up to 4200 lumens

4 foot - 80W, up to 8400 lumens

120-277V, 50/60Hz



Metallic LED VP

Wall (bulkhead) mount
Ceiling mount



UL/cUL Certified to:

- UL1598 Suitable for Wet Locations
- UL 1598A Marine Saltwater
- UL 844 Hazardous Locations

Class I, Division 2 Groups A, B, C, D

Class I, Zone 2 T3A, 180°C maximum surface temperature

Class II, Division 2 Groups F, G

T4A, 120°C maximum surface temperature

IP66, ABS

17W, 1300 lumens

5600K and 3000K options

Sealed in optically clear silicone.

100-277V 0-10V dimming



Conveyo™

Wall or pole mount capable
IP63 rated (wall mount)
IP65 rated (pole mount)



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations

Class I, Division 2 Groups A, B, C, D

Class II, Division 2 Groups F, G

Class III

UV- and impact-resistant PMMA

Type II optic Full cutoff, zero uplight

Standard option 6500 lumens, 5000K

5800 lumens, 3000K 50W

Conquer™ Series Flood

Driverless technology 120 or 277v.
High Temperature up to 85°C



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 844 Hazardous Locations (-40°C to +40°C)

Class I, Division 2 Groups A, B, C, D

T4, 135°C (275°F) maximum surface temperature

Class II, Division 2 Groups F, G

IP67, NEMA 6

10 mm tempered glass - standard

Domed clear or diffuse polycarb lens

60W, 6000 lumens 5000K

COB technology

Wayfinder™

Continuous row mounting (TW)-optional



ETL/cETL Listed (standard fixture) to:

- UL1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)

ETL/cETL Listed EMB option UL 924

CE, ABS, IP66 rated

9W, up to 1100 lumens

pathway/walkway/overdoor light

EMB 2HR (standard) 120 mins

6HR (optional) 360 mins

Cube-Light

Wall (bulkhead) mount
Ceiling mount



ETL/cETL Listed to:

- UL 1598 Wet Locations
- UL 1598A Marine (Saltwater)

CE, ABS, IP66 rated

Impact-resistant, polycarbonate

Red, green, blue and amber

13W, 1000 lumens

Conformal coated

Conquer™ Series Linear

Driverless technology 120 or 277v.
High Temperature up to 85°C



UL/cUL Listed to:

- UL 1598 Wet Locations
- UL 844 Hazardous Locations (-40°C to +55°C)

Class I, Division 2 Groups A, B, C, D

T4, 135°C (275°F) maximum surface temperature

Class II, Division 2 Groups F, G

T4A, 120°C (248°F) maximum surface temperature

Class III

IP67, NEMA

2ft - 60W 6600 lumens

4ft - 80W 4ft 9400 lumens

5000K 120V or 277V

-40°C to +85°C

ReadiLED™ Series

90-minute run time EMB available
on 4-foot model



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598C LED Retrofit Conversion (retrofit kits only)
- UL 1598A Marine (Saltwater)
- UL 924 Emergency Lighting Equipment

ABS, IP65, CE

2 foot - 40W, up to 4200 lumens

4 foot - 80W, up to 8400 lumens

120-277V, 50/60HZ

SLX/SLXP/DLX

Available as Dock Light, Floodlight,
Portable Task Light



ETL/cETL Certified to:

- UL 1598 Ordinary Locations
- UL 1598A (Saltwater)
- UL 844 Suitable for Hazardous Locations

Class I, Division 1 Groups C & D

Class I, Division 2 Groups A, B, C & D

Class II, Divisions 1 & 2 Groups F & G

Class III, Divisions 1 & 2

- NEMA 4X

44W, 3800 lumens 5000K

Conformal coated modules

Flood (45°) and spot (28°)

