



PHOENIX®
DURABILITY X DESIGN™

Command Flood® Series

Marine Grade Floodlight

Patents Pending



Marine-rated floodlight for above-deck lighting

Customized flanking light optics ideal for pushboats

Waterline security light for SYM 303.X




Stainless steel bracket and hardware for maximum corrosion resistance

IP66 and suitable for all demanding marine conditions

Designed and manufactured in the USA

Dimensions

CF-125 Model



This product complies with domestic preference requirements such as BAA or TAA.
For additional information, visit phoenixlighting.com or consult your representative.






Command Flood® Series

Marine Grade Floodlight




PHOENIX®
DURABILITY X DESIGN™

Dimensions

CF-250 Model



CF-375 Model



Specifications

Construction	Marine grade, aluminum housing Adjustable 316 stainless steel mounting harp (SSHRP) Adjustable waterline security bracket (NPL) (CF-125 only)
Finish	Type II anodized finish per MIL-A-8625
Hardware	Marine grade (316) stainless steel
Lens	Weatherproof, clear polycarbonate
Light source	CF-125, 120W, up to 15,300 lumens CF-250, 240W, up to 32,000 lumens CF-375, 360W, up to 48,000 lumens CRI > 70 50,000 hour rated life Cool white LEDs (CW) - standard Neutral white (NW) and warm white (WW) LEDs - contact factory
Power source	120-277V, 50-60Hz 277-480V, 50-60Hz (CF-250 and CF-375 only) Overload, over-voltage, over-temperature and short-circuit protection
Surge protection	6kV line to line; 10kV line to earth 10 kV/kA
Wiring	Stranded wires Optional 17 gauge, 3 conductor cord (CD), 72.00 in (1829 mm) (CF-250 and CF-375 only) 120.00 in (3048 mm) (CF-125 only) Standard cord grip 6 mm - 12 mm (0.24 in - 0.47 in) Optional junction box, without cord (JBOX)
Vibration	5 Grms, 100-2200 Hz
Ambient operating temperature	-40°C to + 50°C Designed for use in areas allowing air flow
Humidity range	0% to 100%
Mounting	Ceiling mount 220° harp rotation
Safety cable	Safety cable included
Weight	CF-125 model - 13.0 lbs (5.9 kg) CF-250 model - 31.4 lbs (14.2 kg) CF-375 model - 44.2 lbs (20 kg)
Warranty	5 years

For IES files, see website or contact factory

Compliances

UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
- CSA C22.2 No. 250.0

ABS

IP66

LM79 and LM80 reports available upon request



Command Flood® Series

Marine Grade Floodlight

PHOENIX®
DURABILITY X DESIGN™

Ordering Information

Example: CF-125-SP-120-277-CW-SSHRP-CD

Fixture	Model	Optic	Voltage	CCT	Mounting Bracket	Wiring
CF	125	VS ²	120-277	CW	SSHRP	JBOX
	250	SP	277-480 ²	NW	NPL ³	CD ⁴
	375	MF		WW ¹		
		WF				

Model		Optic		Voltage		CCT	
125	120W	VS ²	Very narrow spot	120-277	120-277V, 50-60Hz	CW	Cool white
250	240W	SP	Spot	277-480 ²	277-480V, 50-60Hz	NW	Neutral white
375	360W	MF	Medium flood			WW ¹	Warm white
		WF	Wide flood				

Mounting Bracket

SSHRP	Adjustable 316 stainless steel mounting bracket
NPL ³	Adjustable waterline security bracket with SYM 1218.3 plug (replacement for SYM 303.X)

Wiring


JBOX	Junction box, no cord included
CD ⁴	Cord with pigtail (CF-125 model provided with 120.00 in (3048 mm) cord; CF-250 & CF-375 models provided with 72.00 in (1829 mm) cord)

Notes

- 1 Contact factory for lead time
- 2 Only available with CF-250 & CF-375 models
- 3 Only available with CF-125 models
- 4 CD models of CF-250 & CF-375 provided with cord coming out of junction box

Special Projects: We may be able to accommodate your special projects, so please don't hesitate to ask about additional options. Minimum order quantities and/or extended lead times will apply. Contact your Phoenix representative with specific inquiries.

Adjustable Waterline Security Bracket (NPL)



Note: LED replacement for SYM 303.X

Product design and specifications are subject to change without notice.