

ModCom® 3 Series Hazardous Area Flood Light

Robust construction ideal for up to 6G high vibration, high temperature and hazardous applications



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 2 Groups F & G
- Class III

CE, ABS, IP67, IP69K

Up to 15,000 lumens - 121W (LO)


Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



Defend™ Flood 2

Aimable in 15° increments
Mounting ceiling, wall or pendant



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
- UL 844 Hazardous Locations
 - Class I, Division 1 Groups C & D
 - Class I, Division 2 Groups A, B, C, D
 - Class II, Division 1 Groups E, F, G
 - Class II, Division 2 Groups F, G
 - Class III

IP66, IK10, ABS (pending)

5,600 lumens - 40W

8,400 lumens - 60W

14,000 lumens - 100W

28,000 lumens - 200W

120-277V, 277-480V, 1-10V dimming

6kV surge protection

HDL-LED Linear

90-minute run time EMB
1100 lumens



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations
- Class I, Division 2 Groups A, B, C, D
- Class I, Zone 2 Group IIC
- T3C, 160°C maximum surface temperature
- CE, ABS, IP67 rated

HDL1 - 28W, 2850 lumens

HDL2 - 55W, 5700 lumens

HDL3 - 83W, 8550 lumens

120-277V, 277-480V



EcoMod® 3 Series Heavy Duty Flood Light

Expertly engineered with durable, marine grade components and various optic options



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)

CE, IP66, ABS

Up to 15,000 lumens - 121W (LO)

Up to 30,000 lumens - 231W (HI)

Up to 52,500 lumens - 438W (MAX)



LFXB Linear

90-minute run time EMB available
on 4-foot model



UL/cUL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Locations
- Class I, Division 1 Groups C & D
- T6, 85°C maximum surface temperature
- Class II, Division 1 Groups E, F & G
- T3B, 165°C maximum surface temperature
- Class III

- UL 924 Emergency Lighting Equip

2 foot - 40W, up to 4200 lumens

4 foot - 80W, up to 8400 lumens

120-277V, 50/60Hz



Metallic LED VP

Wall (bulkhead) mount
Ceiling mount



UL/cUL Certified to:

- UL1598 Suitable for Wet Locations
- UL 1598A Marine Saltwater
- UL 844 Hazardous Locations
- Class I, Division 2 Groups A, B, C, D
- Class I, Zone 2 T3A, 180°C maximum surface temperature
- Class II, Division 2 Groups F, G
- T4A, 120°C maximum surface temperature
- IP66, ABS
- 17W, 1300 lumens
- 5600K and 3000K options
- Sealed in optically clear silicone
- 100-277V, 0-10V dimming



CVO 2

LED Area & Conveyor Light

Wall or pole mount capable



ETL/cETL Certified to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Outside Type (Saltwater)
Class I, Division 2 Groups A, B, C, D
Class II, Division 2 Groups F & G
Class III, Division 2
T5, 100°C maximum surface temperature
- CSA C22.2 No. 250.0
- CSA C22.2 No. 137

CE

UKCA

IP66

NEMA 4X

DLC

International Dark Sky Association approved (2200K and Amber models only)

FCC Part 15, Subpart B, Class A standards for conducted and radiated emissions

RoHS compliant

In accordance with Chilean regulations of Supreme Decree No. 1 of 2022 (2200K contains less than 7% blue light and Amber contains less than 1% blue light)

Type II (T2), Type III (T3), Type V (T5) optic, Full cutoff, zero uplight

Up to 75W, field adjustable output

Up to 11000 (50K), 8000 (22K) or 6500 (Amber) lumens

ReadiLED™ Series

90-minute run time EMB available
on 4-foot model



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598C LED Retrofit Conversion (retrofit kits only)
- UL 1598A Marine (Saltwater)
- UL 924 Emergency Lighting Equipment

ABS, IP65, CE

2 foot - 40W, up to 4200 lumens

4 foot - 80W, up to 8400 lumens

120-277V, 50/60Hz

Wayfinder™ 2

LED Accessway Light

Integrated EMB option (pending)
Pathway/walkway/overdoor light



UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 924 EMB option (pending)

ABS (pending)

IP66

DLC

3.2W - 11W (field adjustable output), up to 1300 lumens

SubM compliant 2-HR EMB and 6-HR EMB options

Colored (red, green, blue) and diffused lens options

Guard Pro™ Series

Hazardous Rated LED Floodlight



ETL/cEL Certified to:

- UL1598 Suitable for Wet Locations
- UL 1598A Marine (Saltwater)
- UL 844 Hazardous Location
- Class I, Division 2 Groups A, B, C, D
- Class II, Division 1 Groups E, F, G
- Class II, Division 2 Groups F & G
- Class III

IP66, ABS (pending)

Up to 2,600 lumens - 20W (LO)

Up to 5,200 lumens - 40W (LO)

Up to 7,800 lumens - 60W (LO)

Up to 13,000 lumens - 100W (HI)

Up to 19,500 lumens - 150W (HI)

Up to 26,000 lumens - 200W (HI)

SLX/SLXP/DLX

Available as Dock Light, Floodlight,
Portable Task Light



ETL/cETL Certified to:

- UL 1598 Ordinary Locations
- UL 1598A (Saltwater)
- UL 844 Suitable for Hazardous Locations

Class I, Division 1 Groups C & D

Class I, Division 2 Groups A, B, C & D

Class II, Divisions 1 & 2 Groups F & G

Class III, Divisions 1 & 2

- NEMA 4X

44W, 3800 lumens, 5000K

Conformal coated modules

Flood (45°) and Spot (28°)

Cube-Light

Wall (bulkhead) mount
Ceiling mount



ETL/cETL Listed to:

- UL 1598 Wet Locations
- UL 1598A Marine (Saltwater)

CE, ABS, IP66 rated

Impact-resistant, polycarbonate

Red, green, blue and amber

13W, 1000 lumens

Conformal coated